


The Independent PVCu Stockist






Less bars, more light

Aluminium Skylights and Roof Lanterns Slimmer, stronger and fast to install, the all new Maxilite range of aluminium roofs

Maxilite Range



Ask about

Maxi-hipped

- Available in both double and triple glazed options
- No radius ends, slim profiles and just a 60mm ridge
- Maximum size is 3m wide x any length

Maxi-pyramid

- Available in both double and triple glazed options
- No ridge and just four hip beams
- Maximum size is 2.5m x 2.5m
- Designed to fit onto a square opening

Maxi-flat

- Available in both double and triple glazed options
- No visible bars on show internally
- Maximum size is 1.2m x 2.5m

Maxi-sky

- Available in both double and triple glazed options
- ► For large spanning flat opening
- Maximum size is 3m projection x any length

Maxi-opener

- Available in double glazed versions only
- No visible bars on show internally
- 240v and 24v options
- Temperature controlled

Maxi-walk-on

- Available in double glazed only
- 1.2u value to pass building control
- Maximum size is 2m x 1m
- Please note these lanterns are heavy

Maxi-vent

- Available in both double and triple glazed options
- 240v and 24v options
- Manual or electric versions

Bi-Fold Glass Verandas



Glass technology

We glaze all of our roofs with argon gas filled units. The outer pane has a heat reflective coating which reflects 60% of the sun's heat away from your house, yet also retains heat in the building during colder periods, reducing heating bills.

Self Cleaning glass

All of the Maxilite roof lanterns come glazed with self cleaning glass as standard. The outer pane of glass is permanently bonded with a self clean coating which prevents the build up of dirt. When it rains the dirt is dispersed, leaving the glass clean and free of marks.

Argon Gas Filled as standard

MaxiLite

All units are filled with argon gas. Argon is 35% more thermally efficient than air as an insulator. Although argon gas makes the sealed unit more expensive to manufacture it improves its insulation properties by up to 30% over standard air filled units.

Soft Coated low Energy Glass

We only use Low energy soft coated glass in Maxlite roofs. This has benefit of reflecting the external heat of the sun during hot days and also reflecting the heat produced from your homes central heating back into your home when its cold, keeping your heating bills down and reducing CO emissions.

44mm Triple Glazed Units *

Warm Edge Spacer

Argon Gas Filled

Triple Glazing Option

Self Cleaning Glass

We offer a 36mm triple glazed roof glass option, for the Maxi Hipped, Maxi Sky and Maxi Pyramid Roofs. The Maxi Flat has a 44mm triple glazed sealed unit for increased thermal efficiency. By adding an additional layer of low energy glass and an additional argon gas cavity the glass unit's efficiency improves by more than 80%. A triple glazed argon gas filled unit with low energy glass and a warm edge spacer bar has a thermal transfer rating of just 0.7u value, a standard double glazed sealed unit has a thermal rating of 2.4uv.




All Maxilite roofs are glazed with toughened safety glass as standard. The glass is tempered at high temperatures allowing it to withstand greater loads. The tempering also makes it safer to use in roof applications. In this load test, carried out at our factory, we lowered seven 25kg bags of ballast onto a double glazed unit. Please note this is not a walk on roof.




Glazing Options		U Value Double Glazed	U Value Triple Glazed	Solar Heat Re- flection DG	Solar Heat Reflec- tion Triple	Self Clean Coating
Clear		1.0v	0.7u	60%	70%	
Blue		1.0u	0.7u	60%	70%	
Neutral		1.0u	0.7u	78%	82%	
Bronze		1.0u	0.7u	52%	73%	
Privacy		1.0u	0.7u	60%	76%	
Aqua		1.0u	0.7v	60%	35%	

Measure EXTERNAL edges of the roof up-stand




Sizes required

- External sizes required
- Outer edges of up-stand
- Ring beam is 50mm deep
- Min. Up-stand height 50mm
- Min. Up-stand depth 50mm



Conventional Glass





Maxi-Sky Large spanning flat roofs

Maxi-sky roofs are designed for large spanning openings. Able to span 3m using a flush profile self supporting beam system. With a transom width of just 60mm, means less bars and more light.

Maximum Security

Glass Lock Maxi-flat glass cannot be removed

Maxi-flats unique glass lock system means that, once the frame is clicked into place, the glass can no longer be removed form the frame. This unique feature makes the Maxilite flat roof one of the most secure lanterns available.

Patented Glass Lock as Standard



Fitting takes minutes not hours



MaxiLite

" does your roof tick all the boxes ? "

Maxi-Pyramid

Maxi-pyramid lanterns do not require a ridge

Maxi-pyramid roofs are designed to fit onto square roof openings. With no need for a ridge beam, and sloping on all sides, the Maxi-pyramid roof system gives the maximum possible glass area with the minimum obstruction. Designed to fit onto square roof openings, and with just four transoms, gives the maximum light



Maxi-Opener Maxi-openers, the electrically opening flat lantern

Ideal for square openings

Maxi-walk-on

Maxi-walk-on roofs with a 1.2u value



Maxi-hipped

MaxiLite

Super Slim The maxi-hipped roof uses super slim bars

With a ridge width of just 60mm, no bulky radius ends and eliminating the need for jack rafter supports, the Maxi-hipped roof system is one of the slimmest roof lanterns on the market today. Using powder coated aluminium caps externally Maxilite lanterns have a life expectancy in excess of 25 years.

" does your roof tick all the boxes?"



Self Cleaning Glass

Conventional Glass

Self cleaning, 1.0 u value glass as Std. Maxilite roofs come with self cleaning glass unit as standard



MaxiLite

Maxi-vent

Automatic Electric Roof Vents

- Fully automatic lantern roof vents
- Concealed motor option (no wires showing)
- Temperature controlled
- Built in rain sensors
- Remote controlled units
- 240v and 24v options

BI W A A

Black

White

Agate Grey

Anthracite Grey

Super Slim Aluminium Profiles

No Internal or External Radius Ends



Ridge Width Just 60mm







Bath House Road Croydon CR0 4TT

^{6 Beddington Trading Park} **020 8665 1221** Bath House Road

Fax: 020 8665 1444 sales@carltonplastics.co.uk

PVCu Fascia & Soffits Guttering & Down Pipes Cladding and Trims



Conservatory Kit Roofs Polycarbonate & Glass Glazing Bar Systems



PVCu Windows & Doors Bi-Fold & Patio Doors Composite Doors

PVCu Window Boards Architraves & Trims Silicones & Fixings